

TOTAL FIREBALL GRINDING WHEELS



MILLIMETERS TO INCHES CONVERSION TABLE		
145 mm = 5-11/16"	100 mm = 3-15/16"	22 mm = 7/8"
16 mm = 5/8"	10 mm = 25/64"	7.9 mm = 5/16"
6 mm = 15/64"	4.7 mm = 3/16"	3.2 mm = 1/8"

Click on Part Number to Purchase

Bell

SUITABLE FOR MODEL(S)	SIZE	USE FOR	WHEEL TYPE*	NO.
K50, K100B, K150, KB1, KB1A, KB12	4" x 3/8" x 1/8"	1/4, 3/8 L.P., .325	R	BD180
	4" x 3/8" x 3/16"	3/8, .404	R	BD175
	4" x 3/8" x 7/32"	.404, 1/2	V	BD182
	4" x 3/8" x 1/4"	Depth gauges	R	BD186R
KB101, KB125, K200	6" x 1/2" x 1/8"	1/4, .325, .354	R	BD255
	6" x 1/2" x 3/16"	3/8, .404	R	BD257
K245, K246	5" x 3/8" x 1/8"	1/4, 3/8 L.P., .325	R	BD193
	5" x 3/8" x 3/16"	3/8, .404	R	BD194
	5" x 3/8" x 1/4"	Depth gauges	R	BD195R
Peerless model	6" x 3/4" x 1/8"	1/4, 3/8 L.P., .325	R	BD238
	6" x 3/4" x 3/16"	3/8, .404	V	BD245

Besaw/Efco/Tecomec/Total

SUITABLE FOR MODEL(S)	SIZE	USE FOR	WHEEL TYPE*	NO.
Besaw: 8800 Efco: FL-6, FL136 Tecomec: Jolly, Jolly Deluxe, Super Jolly, Jolly Star, TM11369001 Total: TL136, TL150, TL900	145 x 22 x 6mm	Depth gauges	V	TL65
	5" x 22mm x 1/8"	1/4", 3/8 L.P., .325	B**	TL66B
	5" x 22mm x 3/16"	3/8, .404	B**	TL64B
	5" x 22mm x 5/16"	Depth gauges	B**	TL65B
	145 x 22 x 3.2mm	1/4, 3/8 L.P., .325	V	TL66
	145 x 22 x 3.2mm	1/4, 3/8 L.P., .325	R	TL66-R
	145 x 22 x 4.7mm	3/8, .404	V	TL64
	145 x 22 x 4.7mm	3/8, .404	R	TL64-R
	145 x 22 x 7.9mm	3/4, depth gauges	V	TL516
	Tecomec: Mini-Jolly Total: TL135, TL185	100 x 16 x 3.2mm	1/4, .325	V
100 x 16 x 4.7mm		3/8, .404	V	1185-149
100 x 16 x 6mm		1/2, depth gauges	V	1185-150
100 x 16 x 10mm		3/4, guard link depth gauges	V	1185-055GL
Tecomec: Baby Jolly, Midi Jolly, Easy Grinder, TM1190925 Total: TL190, TL195, TL195-120	105 x 22 x 3.2mm	1/4, .325, 3/8 L.P.	V	1190-051
	105 x 22 x 4.7mm	3/8, .404	V	1190-052
	105 x 22 x 6mm	depth, gauges (rakers)	V	1190-053

Foley

SUITABLE FOR MODEL(S)	SIZE	USE FOR	WHEEL TYPE*	NO.
307, 308	5" x 1/2" x 1/8"	1/4, 3/8 L.P., .325	R	F370588
	5" x 1/2" x 3/16"	3/8, .404	R	F370587
	5" x 1/2" x 1/4"	7/16, 1/2	R	F370589
	5" x 1/2" x 5/16"	Depth gauges and 3/4 cutters	R	F370576

*WHEEL TYPES

V=VITRIFIED Premium-grade. Very hard and long-lasting.

R=RESINOID Softer, low-resistance wheel. Prevents cutter "Burning".

B=BORAZON Super-premium grade. Long-lasting. Higher cost.



**NOTE

These Borazon wheels are for regular wood cutting saw chain without carbide cutters.

TOTAL FIREBALL GRINDING WHEELS



MILLIMETERS TO INCHES CONVERSION TABLE		
145 mm = 5-11/16"	100 mm = 3-15/16"	22 mm = 7/8"
16 mm = 5/8"	10 mm = 25/64"	7.9 mm = 5/16"
6 mm = 15/64"	4.7 mm = 3/16"	3.2 mm = 1/8"

Oregon

SUITABLE FOR MODEL(S)	SIZE	USE FOR	WHEEL TYPE*	NO.
511A, 109179	145 x 22 x 6mm	Depth gauges	V	TL65
	5" x 22mm x 1/8"	1/4", 3/8 L.P., .325	B**	TL66B
	5" x 22mm x 3/16"	3/8, .404	B**	TL64B
	5" x 22mm x 5/16"	Depth gauges	B**	TL65B
	145 x 22 x 3.2mm	1/4, 3/8 L.P., .325	V	TL66
	145 x 22 x 3.2mm	1/4, 3/8 L.P., .325	R	TL66-R
	145 x 22 x 4.7mm	3/8, .404	V	TL64
	145 x 22 x 4.7mm	3/8, .404	R	TL64-R
	145 x 22 x 7.9mm	3/4, Depth Gauges	V	TL516
	105 x 22 x 4.7mm	3/8, .404	V	1190-052
108181, 109178, 109716	105 x 22 x 3.2mm	1/4, .325, 3/8	V	1190-051
	105 x 22 x 6mm	depth, gauges (rakers)	V	1190-053

Silvey

SUITABLE FOR MODEL(S)	SIZE	USE FOR	WHEEL TYPE*	NO.
300	5-3/4" x 1" x 1/4"	Depth gauges	V	SG34
	5-3/4" x 1" x 1/8"	1/4, 3/8 L.P., .325	V	SG38
	5-3/4" x 1" x .155"	3/8, .404	V	SG315
500, 600	8" x 1" x 1/8"	1/4, 3/8 L.P., .325	V	SN0218
	8" x 1" x .155"	3/8, .404	V	SN02115
	8" x 1" x 3/16"	Depth gauges	V	SN021

Stihl

SUITABLE FOR MODEL(S)	SIZE	USE FOR	WHEEL TYPE*	NO.
All Models	140 x 12 x 4.5mm	3/8, .404	V	TL63
	140 x 12 x 3.2mm	1/4, 3/8 L.P., .325	V	TL62
	120 x 12 x 9mm	Depth gauges	V	TL61

Windsor

SUITABLE FOR MODEL(S)	SIZE	USE FOR	WHEEL TYPE*	NO.
30 - 1110, A225	145 x 22 x 6mm	Depth gauges	V	TL65
	5" x 22mm x 1/8"	1/4", 3/8 L.P., .325	B**	TL66B
	5" x 22mm x 3/16"	3/8, .404	B**	TL64B
	5" x 22mm x 5/16"	Depth gauges	B**	TL65B
	145 x 22 x 3.2mm	1/4, 3/8 L.P., .325	V	TL66
	145 x 22 x 3.2mm	1/4, 3/8 L.P., .325	R	TL66-R
	145 x 22 x 4.7mm	3/8, .404	V	TL64
	145 x 22 x 4.7mm	3/8, .404	R	TL64-R
	145 x 22 x 7.9mm	3/4, Depth Gauge	V	TL516

*WHEEL TYPES

V=VITRIFIED Premium-grade. Very hard and long-lasting.

R=RESINOID Softer, low-resistance wheel. Prevents cutter "Burning".

B=BORAZON Super-premium grade. Long-lasting. Higher cost.



**NOTE

These Borazon wheels are for regular wood cutting saw chain without carbide cutters.